

PISTOL GRIP NUTRUNNERS

Torque control type

LTP61 H/HR

Bolt capacity M12 – M42

The LTP61 features the same twin motor concept as the LTP51 range. The main difference is the speed – the rundown is twice as fast as the LTP51.

All other features, such as high torque accuracy and extremely high torque output to weight ratio, are the same.

In addition you get a reversible tool that has fixed positions for both forward and reverse.



Model	Bolt size mm	Square drive in	Torque range at 6.3 bar		Min torque at 3 bar		Free speed r/min	Weight ^a		Length mm	CS distance mm	Air consumption at free speed		Air inlet thread in	Spline type	Ordering No.
			Nm	ft lb	Nm	ft lb		kg	lb			l/s	cfm			
Non reversible																
LTP61 H100-13	M12	1/2	55 - 100	40 - 75	45	35	1800	3.0	6.6	223	29	20	42	3/8	3	8431 0800 07
LTP61 H170-13	M14	1/2	95 - 170	70 - 125	70	50	1100	3.0	6.6	223	29	20	42	3/8	3	8431 0800 14
LTP61 H230-19	M16	3/4	125 - 230	90 - 170	85	60	820	3.0	6.6	223	29	20	42	3/8	3	8431 0800 21
LTP61 H350-20	M18	3/4	190 - 350	140 - 255	145	105	520	3.9	8.6	260	31	20	42	3/8	4	8431 0800 28
LTP61 H500-20	M20	3/4	275 - 500	200 - 370	220	160	360	3.9	8.6	260	31	20	42	3/8	4	8431 0800 35
LTP61 H700-25	M22	1	360 - 650	265 - 480	280	207	280	4.5	9.9	305	34	20	42	3/8	5	8431 0800 42
LTP61 H900-25	M24	1	480 - 870	350 - 640	300	220	210	4.5	9.9	282	32	20	42	3/8	5	8431 0800 49
LTP61 H1500-25	M30	1	850 - 1500	625 - 1100	700	516	115	6.8	14.5	323	42	20	42	3/8	9	8431 0800 56
LTP61 H1900-38	M30	1 1/2	1050 - 1900	770 - 1400	800	576	90	14.1	31.0	380	68	20	42	3/8	8	8431 0800 63
LTP61 H2800-38	M36	1 1/2	1550 - 2800	1140 - 2060	1200	864	65	14.1	31.0	380	68	20	42	3/8	8	8431 0800 70
LTP61 H3800-38	M42	1 1/2	2100 - 3800	1540 - 2790	1600	1152	50	14.1	31.0	380	68	20	42	3/8	8	8431 0800 77
Reversible																
LTP61 HR100-13	M12	1/2	55 - 100	40 - 75	45	35	1800	3.0	6.6	235	30	20	42	3/8	3	8431 0801 08
LTP61 HR170-13	M14	1/2	95 - 170	70 - 125	70	50	1100	3.0	6.6	238	30	20	42	3/8	3	8431 0801 15
LTP61 HR230-19	M16	3/4	125 - 230	90 - 170	85	60	820	3.0	6.6	275	34	20	42	3/8	3	8431 0801 22
LTP61 HR350-20	M18	3/4	190 - 350	140 - 255	145	105	520	3.9	8.6	275	34	20	42	3/8	4	8431 0801 29
LTP61 HR500-20	M20	3/4	275 - 500	200 - 370	220	160	360	3.9	8.6	275	34	20	42	3/8	4	8431 0801 36
LTP61 HR700-25	M22	1	360 - 650	265 - 480	280	207	280	4.5	9.9	305	34	20	42	3/8	5	8431 0801 43
LTP61 HR900-25	M24	1	480 - 870	350 - 640	300	220	210	4.5	9.9	305	34	20	42	3/8	5	8431 0801 50
LTP61 HR1500-25	M30	1	850 - 1500	625 - 1100	700	516	115	6.8	14.5	345	42	20	42	3/8	9	8431 0801 57
LTP61 HR1900-38	M30	1 1/2	1050 - 1900	770 - 1400	800	576	90	14.1	31.0	380	68	20	42	3/8	8	8431 0801 64
LTP61 HR2800-38	M36	1 1/2	1550 - 2800	1140 - 2060	1200	864	65	14.1	31.0	380	68	20	42	3/8	8	8431 0801 71
LTP61 HR3800-38	M42	1 1/2	2100 - 3800	1540 - 2790	1600	1152	50	14.1	31.0	380	68	20	42	3/8	8	8431 0801 78

^a Without reaction bar.
Recommended hose size: 13 mm
Sound level: 79 dB(A)

LTP61 H/HR: Change over torque is around 7% of maximum torque on a given air pressure.

ACCESSORIES INCLUDED

LTP61: Swivel type reaction bar

OPTIONAL ACCESSORIES

Page 67-68



SELECTED SERVICE KITS

Page 68